

Cat8 S/FTP Data Cable

APPLICATION

- All Ethernet applications which includes 10/100/1000 Base T or 1000 Base TX, 10 G Base – T, 25G and 40G Base –T
- Suitable for switch to server connection in Data Centers application till 2000 MHz
- 30 Meter Channel performance complied to ANSI/TIA 568C.2.1

Conductor:	22 AWG Solid bare Copper
Insulation:	Foam High Density Polyethylene
Pairs:	2 Insulated conductors twisted together
Shield:	Individual Pair Shielded with Aluminum / Polyester Foil
Overall Shield:	Tinned Copper Braiding with 40% Min braiding Coverage
Sheath:	LSZH
Cable Diameter:	8.5+ 0.3 mm
Printing:	Each meter printed with

25 years system warranty available

APPLICATION

Flame Retardant comply to IEC 60332 P1/P2
Halogen Free Comply to IEC 60754 P1

CABLE FEATURES



- Individual Foil shield gives higher protection against cross talk
- Overall shield reduces EMI

CABLE COLOR

Cable is available in
Grey , Natural, Violet colors.

CONNECTION SYSTEM

Compatible with all common systems according to ISO/IEC 11801: 2011



COLOUR CODE

PAIR	SPECIFICATIONS
1	Blue / White – Blue
2	Orange / White - Orange
3	Green / White - Green
4	Brown / White - Brown

ELECTRICAL PROPERTIES

D.C Loop Resistance	< 2.4 /30m
Resistance Unbalance	: 4% Max
Delay Skew	< 13.5 nS

MECHANICAL PROPERTIES

Bending Radius	< 8 x Cable Diameter
Pulling Force	11.5kg
Temperature Range	-20° to +70°C



Cat8 S/FTP Data Cable

TRANSMISSION/CHARACTERISTICS - 100M

Frequency	RL(dB) Min.	IL(dB) Max.	NEXT (Min) dB	PSNEXT(dB) Min.	ACRF(dB) Min.	PSACRF (dB) Min.	Prop.Delay (Max) ns / 30 m
1	20.0	2.0	75.3	72.3	79.0	76.0	171.0
4	23.0	2.0	66.3	63.3	67.0	64.0	165.5
8	24.5	2.0	61.8	58.8	60.9	57.9	163.9
10	25.0	2.0	60.3	57.3	59.0	56.0	163.5
16	25.0	2.2	57.2	54.2	54.9	51.9	162.8
20	25.0	2.5	55.8	52.8	53.0	50.0	162.5
25	25.0	2.8	54.3	51.3	51.0	48.0	162.2
31.25	25.0	3.1	52.9	49.9	49.1	46.1	162.0
62.5	23.6	4.4	48.4	45.4	43.1	40.1	161.4
100	22.2	5.6	45.3	42.3	39.0	36.0	161.1
200	20.1	7.9	40.8	37.8	33.0	30.0	160.8
250	19.4	8.9	39.3	36.3	31.0	28.0	160.7
300	18.9	9.8	38.1	35.1	29.5	26.5	160.6
400	18.0	11.4	36.3	33.3	27.0	24.0	160.6
500	17.3	12.8	34.8	31.8	25.0	22.0	160.5
600	16.8	14.1	33.6	30.6	23.4	20.4	160.4
1000	15.2	18.6	30.3	27.3	19.0	16.0	160.3
1500	14.0	23.2	27.7	24.7	15.5	12.5	160.3
2000	13.1	27.2	25.8	22.8	13.0	10.0	160.2

ORDER INFORMATION

PART NO.	PRODUCT DESCRIPTION	OUTER DIAMETER (MM)
MK-C8SF22L	CAT8 4x2x22 AWG S/FTP, LSZH	8.5

PACKAGING
305m - Reel
As per customer requirement

USA & CANADA

Tel +1-877-6774040
 info@microlinknet.com
 70 East Sunrise Highway Valley Stream,
 NY 11581, New York

EUROPE

Tel +44-20-37695558
 uk@microlinknet.com
 4th Floor, 18 St. Cross Street,
 London, EC1N 8UN

MIDDLE EAST

Tel +971 4 556 1557
 mena@microlinknet.com
 Boulevard Plaza Tower One, Level 3,
 Downtown Dubai, United Arab Emirates

