

Fiber Optic, Drop cable, Outdoor, 2-4 fibers

DESCRIPTION

MICROLINK FTTH Drop Cable is made of 1 to 4, 250µm individually colored optical fibers with fiber reinforced strength members, steel wire which also acts as messenger wire and UV resistant Low Smoke Zero Halogen (LSZH) or PE jacket. The steel wire provides additional strength suitable for aerial applications.

FEATURES AND BENEFITS

- ✓ Fiber-count 2 and 4 fibers
- ✓ Single mode options available
- ✓ Compact cable construction
- ✓ FRP strength member
- ✓ Suitable for tight corners and bends
- ✓ Metal messenger wire
- ✓ Individually colored optical fibers
- ✓ Conforms to IEC, TIA and Telcordia standards
- ✓ Standard cable length of 2km

STANDARDS

ITU.T G.652D / G.657A/B
IEC 60332-1-2, IEC 60754-1,2 & IEC 61034-2

APPLICATIONS

FTTx applications
CCTV

ENVIRONMENTAL DATA

Temperature Range	Value
Service	- 20° C to +70° C

CABLE CONSTRUCTION

2 core drop cable	01 – Blue	02 – Orange	-	-
4 core drop cable	01 – Blue	02 – Orange	03 - Green	04 - Brown



