

CAT5e F/UTP - Data Cable

PRODUCT DESCRIPTION

24 AWG copper wire insulated with Polyethylene. Two insulated conductors twisted together to form a pair and four such pairs laid up to form the core unit covered with a Aluminum Polyester tape, overall jacketed with PVC/LSZH. Enhanced performance cable enables delivering high speed.

FEATURES

Flame Rating

PVC-CM

LSZH-IEC 60332-1; IEC 60754 1&2; IEC 61034-2

Very good RFI/EMI interference attenuation to enable installation to high electrical noise locations

Specified and tested upto 100MHz

Compliant to american standard ANSI/TIA 568-C.2,

International standard ISO/IEC 11801 Class D

25 years system warranty available

PRODUCT APPLICATION

10 Base T (IEEE 802.3)

100 Base T (IEEE 802.3U)

1000 BASE-T (IEEE 802.3ab)

TP-PMD (ANSI X3T9.5)

100 Mbps CDDI

ATM 155

4/16 Mbps Token Ring (IEEE 802.5)

Meets IEEE802.3af & 802.3at PoE



JACKET COLOURS

Blue, Grey or Customer Specific Colours



UL Listed CM, CMR, CMX @ 75°C., ETL Verified

Certification is applicable to specific product part no.



COLOUR CODE

PAIR	SPECIFICATIONS
1	Blue - White Blue
2	Orange - White Orange
3	Green - White Green
4	Brown - White Brown

PRODUCT SPECIFICATION

Mechanical & Environmental Characteristics

CHARACTERISTIC	SPECIFICATIONS
Maximum tensile load	110 N (installation)
Minimum bend radius	8 x cable outer diameter
Temperature	0°C to +50°C (installation) -10°C to +60°C (operation)



CAT5e F/UTP - Data Cable

TRANSMISSION/CHARACTERISTICS - 100M

Characteristics	Frequency (Mhz)	1.00	4.00	8.00	10.00	16.00	20.00	25.00	31.25	62.50	100
Return loss (dB)	Spec (Min)	20.0	23.0	24.5	25.0	25.0	25.0	24.3	23.6	21.5	20.1
Insertion loss(dB)	Spec (Max)	2.0	4.1	5.8	6.5	8.2	9.3	10.4	11.7	17.0	22.0
NEXT (dB)	Spec (Min)	65.3	56.3	51.8	50.3	47.2	45.8	44.3	42.9	38.4	35.3
PSNEXT (dB)	Spec (Min)	62.3	53.3	48.8	47.3	44.2	42.8	41.3	39.9	35.4	32.3
ELFEXT (dB)	Spec (Min)	63.8	51.8	45.7	43.8	39.7	37.8	35.8	33.9	27.9	23.8
PSELFEXT (dB)	Spec (Min)	60.8	48.8	42.7	40.8	36.7	34.8	32.8	30.9	24.9	20.8
ACR (dB)	Spec (Min)	63.3	52.2	46.0	43.8	39.0	36.5	33.9	31.2	21.4	13.3

ELECTRICAL PROPERTIES @20 DEG C

CHARACTERISTICS	SPECIFICATIONS
Characteristic Impedance	100+/- 15 Ohms @ 100MHz
Conductor Resistance	Max 9.38 Ohms/100M
Conductor Resistance Unbalance	Max 5%
Mutual Capacitance	5.6nF/100m
Delay Skew	Max 45 ns/100m @ 100MHz
Propagation Delay	< 536 ns/100m @ 100MHz

PACKAGING
305m - Reel
500m / 1000m - Reel

PART NO.	PRODUCT DESCRIPTION	Outer Diameter (mm nom.)
MK-C5FU24P	Cat 5e 4x2x24 AWG S/FTP, PVC	7.0
MK-C5FU24P	Cat 5e 4x2x24 AWG S/FTP, LSZH	7.0



Flame Retardant



Electromagnetically Shielded / Dielectric

USA & CANADA

Tel +1-646-8512555
info@microlinknet.com
70 East Sunrise Highway Valley Stream,
NY 11581, New York

EUROPE

Tel +44-20-37695558
uk@microlinknet.com
4th Floor, 18 St. Cross Street,
London, EC1N 8UN

MIDDLE EAST

Tel +971-4-5561554
mena@microlinknet.com
Building 11, Level 7, Bay Square,
Business Bay, Dubai, UAE

