

CAT6A F/FTP - Data Cable

PRODUCT DESCRIPTION

23 AWG copper wire insulated with Polyethylene. Two insulated conductors twisted together to form a pair and four such pairs covered by a Aluminum polyester tape form the core unit, overall jacketed with flame retardant PVC/LSZH. Enhanced performance cable enables delivering high speed network.

FEATURES

Flame Rating

PVC-CM

LSZH-IEC 60332-1; IEC 60754 1&2; IEC 61034-2

Excellent RFI/EMI interference attenuation to enable installation in high electrical noise locations.

Specified and tested upto 500MHz or higher if Required Compliant to American Standard ANSI/TIA 568-C.2 Cat6a,

International Standard ISO/IEC 11801 Class E

25 years system warranty available

PRODUCT APPLICATION

10G BASE-T (IEEE 802.3)

1000 BASE-T (IEEE 802.3ab)

1000 BASE-TX

Data center I/O consolidation

Back Bone aggregation

Consolidation of network interconnects


Parallel processing and High Speed Computing

Other Legacy LAN and application Video, BAS

Meets IEEE802.3af & 802.3at PoE

JACKET COLOURS

Blue, Grey, Green, Orange Yellow, Violet or Customer Specific Colours



COLOUR CODE

PAIR	SPECIFICATIONS
1	Blue - White or white with color stripe
2	Orange - White or white with color stripe
3	Green - White or white with color stripe
4	Brown - White or white with color stripe

PRODUCT SPECIFICATION

Mechanical & Environmental Characteristics

CHARACTERISTIC	SPECIFICATIONS
Maximum tensile load	110 N (installation)
Minimum bend radius	8 x cable outer diameter
Temperature	0°C to +50°C (installation) -10°C to +60°C (operation)



CAT6A F/FTP - Data Cable

TRANSMISSION/CHARACTERISTICS - 100M

Frequency (Mhz)	Max attenuation (dB/100m)	RL (dB)	NEXT (dB)	PSNEXT (dB)	ACRF (dB)	PSACRF (dB)
1	2.1	20.0	74.3	72.3	67.8	64.8
4	3.8	23.0	65.3	63.3	55.8	52.8
10	5.9	25.0	59.3	57.3	47.8	44.8
16	7.5	25.0	56.2	54.2	43.7	40.7
20	8.4	25.0	54.8	52.8	41.8	38.8
31.25	10.5	23.6	51.9	49.9	37.9	34.9
62.5	15	21.5	47.4	45.4	31.9	28.9
100	19.1	20.1	44.3	42.3	27.8	24.8
200	27.6	18.0	39.8	37.8	21.8	18.8
250	31.1	17.3	38.3	36.3	19.8	16.8
300	34.3	16.8	37.1	35.1	18.3	15.3
500	45.3	15.2	33.8	31.8	13.8	10.8

ELECTRICAL PROPERTIES @20 DEG C

CHARACTERISTICS	SPECIFICATION
Characteristic Impedance	100+/- 15 Ohms
Conductor Resistance	Max < 9.38 Ohms/100m
Conductor Resistance Unbalance	Max 5%
Mutual Capacitance	5.6nF/100m
Delay Skew	Max 45 ns/100m
Propagation Delay	< 536 ns/100m @ 500MHz

STERLITE P/N	PRODUCT DESCRIPTION	OUTTER DIAMETER (MM NOM.)
MK-C6AFF23P	Cat 6a 4x2x23 AWG F/FTP, PVC	7.8
MK-C6AFF23L	Cat 6a 4x2x23 AWG F/FTP, LSZH	7.8

PACKAGING

305m - Reel
500m / 1000m - Reel



Flame Retardant



Electromagnetically Shielded / Dielectric

USA & CANADA

Tel +1-646-8512555
info@microlinknet.com
70 East Sunrise Highway Valley Stream,
NY 11581, New York

EUROPE

Tel +44-20-37695558
uk@microlinknet.com
4th Floor, 18 St. Cross Street,
London, EC1N 8UN

MIDDLE EAST

Tel +971-4-5561554
mena@microlinknet.com
Building 11, Level 7, Bay Square,
Business Bay, Dubai, UAE

